

MOTOR ARM PARTS

Motor Arm Clamping Bolt (2-4039-1) and nut will be included at no extra charge with Motor Arms that require them.

| Make | Control Motor Model | Motor Arm Part No. | Bushing Part No. | Motor Arm Assembly ^① (see page 1) | |
|-----------------------------|--|--------------------------|------------------|---|------------------|
| | | | | For APV, 1813M, 1126, and 1124 | For Wafer Valves |
| Barber Colman | EA 21 to 24 EA 51 to 58 | 2-4028-1 | 2-4125-1 | 2-4078-1 | 2-4313-1 |
| | EA 71 to 76 | 2-4028-1 | — | 2-4078-1 | 2-4313-1 |
| Beck | 2006 2026 26 & 1126 2501 -0 to -3 2521 & Fig. 4 B & C 2522 | 2-4031-1 | — | 2-4078-2 | — |
| | 2702 all other 2722 valves 11-100 | 2-4028-1 | — | 2-4078-1 | 2-4313-1 |
| | GPE (was Askania) | 60-K | 2-3640-1 | 2-3639-1 ^② | — |
| Hoffman (was Schade or ATC) | Type 2 | 2-3791-1 | — | — | — |
| | Type 7 | 2-4031-1 | 2-2431-1 | 2-4078-2 | 2-4313-1 |
| Honeywell | M618, M72, M91, M928, M418 MR-7006 | 2-4028-1 | 2-4102-1 | 2-4078-1 | 2-4313-1 |
| | M-630A, M-640, M-930A, M-940 | 2-4028-1 | 2-4679-1 | 2-4078-1 | 2-4313-1 |
| | 831-E1, 831-E2 | 2-4028-1 | — | 2-4078-1 | 2-4313-1 |
| Honeywell | 010211 to 010218 010261 to 010268 | 2-4028-1 ① | 2-4125-1 ① | 2-4078-1 — | 2-4313-1 — |
| | Penn | M80, M81, & MA Series | 2-4028-1 | 2-4102-1 | 2-4078-1 |
| West | AA-0700 Series | 2-4028-1 | 2-4102-1 | 2-4078-1 | 2-4313-1 |
| Wheelco | Throttletrol | 2-4028-1 | 2-4102-1 | 2-4078-1 | 2-4313-1 |

① For old style L&N, when ordering linkage, replace ¼-20 Rod End Bolt (Motor End) with 1 Swivel Bolt (2-3792-1). For new style L&N, when ordering linkage, add Spacer 2-3269-2, Hex Head Screw R066-3470 and Linkage Adapter 2-9634-1 for Wafer Valves or 2-9634-2 for Adjustable Port or Butterfly Valves.

② Side-by-side valves require a second connecting rod. See Motor End Linkage parts for Adj. Port Valves.

③ Length given is overall length of ⅝" hex rod including ⅝" of ¼-28 thread.

④ Motor Arm Assembly does not include bushing. Order appropriate bushing separately, if required.

⑤ Length given is overall length of ⅝" hex rod including 1" of ⅜-24 thread.

⑥ Included on valves ordered less linkage. Deduct when specifying "less swivel."

⑦ 2 required.

⑧ "X" in part number is to be replaced with number of inches length required for connecting rod--as 2-5019-13 for Linkage Assembly with 14" rod for Adjustable Port Valve.