

VALVES FOR STEAM

(UL listed and CSA certified)
Dimensions (inches)

| North American R- Number | NPT | Max. OPD (psi) | Min. OPD (psi) | Max. Fluid Temp. F | C _v | Enclosure Type | Body Mat. |
|--------------------------|-----|----------------|----------------|--------------------|----------------|----------------|-----------|
| R950-6302 | ¼ | 110 | - | 344 | .52 | NEMA 4 | Brass |
| R950-6305 | ⅜ | 125 | 5 | 353 | 3 | NEMA 4 | Brass |
| R950-6308 | ½ | 125 | 5 | 353 | 4 | NEMA 4 | Brass |
| R950-6310 | ¾ | 125 | 5 | 353 | 5 | NEMA 4 | Brass |
| R950-6315 | 1 | 125 | 5 | 353 | 13.5 | NEMA 4 | Brass |
| R950-6318 | 1¼ | 125 | 5 | 353 | 15 | NEMA 4 | Brass |
| R950-6320 | 1½ | 125 | 5 | 353 | 22.5 | NEMA 4 | Brass |
| R950-6322 | 2 | 125 | 5 | 353 | 43 | NEMA 4 | Brass |
| R950-6325 | 2½ | 125 | 5 | 353 | 45 | NEMA 4 | Brass |

Note: Please specify voltage when ordering. 120/60, 240/50

VALVES FOR AIR

(UL listed and CSA certified)
Dimensions (inches)

| North American R- Number | NPT | Max. OPD (psi) | Min. OPD (psi) | Max. Fluid Temp. F | C _v | Enclosure | Body Type |
|--------------------------|-----|----------------|----------------|--------------------|----------------|--------------|-----------|
| R950-6402 | ¼ | 180 | - | 180 | .5 | NEMA 4 | Brass |
| R950-6405 | ⅜ | 150 | - | 180 | 3 | NEMA 4 | Brass |
| R950-6408 | ⅜ | 125 | 5 | 125 | 3.5 | NEMA 4 | Alum |
| R950-6410 | ½ | 150 | - | 180 | 4 | NEMA 4 | Brass |
| R950-6412 | ½ | 125 | 5 | 125 | 4.8 | NEMA 4 | Alum |
| R950-6415 | ¾ | 150 | - | 180 | 5 | NEMA 4 | Brass |
| R950-6418 | ¾ | 125 | 5 | 125 | 5.1 | NEMA 4 | Alum |
| R950-6420 | 1 | 150 | 5 | 150 | 13 | NEMA 4 | Brass |
| R950-6422 | 1 | 25 | - | 125 | 21 | NEMA 3, 7, 9 | Alum |
| R950-6425 | 1¼ | 150 | 5 | 180 | 15 | NEMA 4 | Brass |
| R950-6428 | 1¼ | 25 | - | 125 | 32 | NEMA 3, 7, 9 | Alum |
| R950-6430 | 1½ | 150 | 5 | 180 | 22.5 | NEMA 4 | Brass |
| R950-6432 | 1½ | 25 | - | 125 | 35 | NEMA 3, 7, 9 | Alum |
| R950-6435 | 2 | 150 | 5 | 180 | 43 | NEMA 4 | Brass |
| R950-6438 | 2 | 25 | - | 125 | 60 | NEMA 3, 7, 9 | Alum |
| R950-6440 | 2½ | 150 | 5 | 180 | 45 | NEMA 4 | Brass |
| R950-6442 | 2½ | 5 | - | 125 | 117 | NEMA 3, 7, 9 | Alum |
| R950-6445 | 3 | 5 | - | 125 | 138 | NEMA 3, 7, 9 | Alum |

Note: Please specify voltage when ordering. 120/60, 240/50
All valves quoted are for AC voltages. Consult sales engineer for price for DC.

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com
T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com



fives
Industry can do it