

Parts Numbers for Specials | Automatic Shutoff Valves

Table 1: 1518/1519 Ordering
check all that apply

Valve Size	Flow Capacity	Body Connection	Body Seals & Bumper Material	Body Material	Internal Trim Package
<input type="checkbox"/> ¾"	<input type="checkbox"/> Standard capacity	<input type="checkbox"/> ANSI (NPT) Threaded	<input type="checkbox"/> Buna O-rings and Buna bumper	<input type="checkbox"/> Cast Iron	<input type="checkbox"/> Trim package 1
<input type="checkbox"/> 1"	<input type="checkbox"/> CP body construction	<input type="checkbox"/> ANSI flanged (PN20) 150#	<input type="checkbox"/> Viton O-rings and Buna bumper	<input type="checkbox"/> Carbon Steel	<input type="checkbox"/> Trim package 2
<input type="checkbox"/> 1¼"	<input type="checkbox"/> High capacity	—	<input type="checkbox"/> Viton O-rings and Viton bumper	<input type="checkbox"/> Stainless Steel	—
<input type="checkbox"/> 1½"	—	—	<input type="checkbox"/> Omniflex O-rings and Buna bumper	—	—
<input type="checkbox"/> 2"	—	—	<input type="checkbox"/> Omniflex O-rings and Viton bumper	—	—
<input type="checkbox"/> 2½"	—	—	—	—	—
<input type="checkbox"/> 3"	—	—	—	—	—
<input type="checkbox"/> 4"	—	—	—	—	—
<input type="checkbox"/> 6"	—	—	—	—	—

Reset	Solenoid or Circuit Voltage	Motor Voltage (Leave blank for manual reset)	Opening Time	Switch Option	Enclosure Rating
<input type="checkbox"/> Manual (Standard handle option)	<input type="checkbox"/> 115VAC/50Hz	<input type="checkbox"/> 115VAC/50Hz	<input type="checkbox"/> None (Manual only)	<input type="checkbox"/> None	<input type="checkbox"/> NEMA 4
<input type="checkbox"/> Automatic	<input type="checkbox"/> 115VAC/60Hz	<input type="checkbox"/> 115VAC/60Hz	<input type="checkbox"/> 2.5 seconds	<input type="checkbox"/> VOS1/VCS1	<input type="checkbox"/> NEMA 4X
	<input type="checkbox"/> 230VAC/50Hz	<input type="checkbox"/> 230VAC/50Hz	<input type="checkbox"/> 6 seconds	<input type="checkbox"/> VOS2/VCS2	—
	<input type="checkbox"/> 230VSC/60Hz	<input type="checkbox"/> 230VAC/60Hz	<input type="checkbox"/> 12 seconds	<input type="checkbox"/> VOS2/VCS1	—
	<input type="checkbox"/> 208VAC/50Hz	<input type="checkbox"/> 208VAC/60Hz	—	—	—
	<input type="checkbox"/> 24VDC	<input type="checkbox"/> 24VDC	—	—	—
	<input type="checkbox"/> 120VDC	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com
T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com



fives
Industry can do it