

FEATURE: The 1615- H, K, M, P, S thru Z versions provide an adjustable input signal override function. When "P" is powered with line voltage the motor will override all input control signals and move to a preset position that is adjustable on a potentiometer mounted on the circuit board.

BENEFIT: This feature could be used as a simple low fire hold. The feature could also be used during an alarm condition, returning the motor to the preset position.

FEATURE: The 1615- H, K, M, P, S thru Z versions have the possibility to operate in split range mode working with any of the following inputs: 4-12, 12-4, 12-20 and 20-12 mA.

BENEFIT: Although some competitive actuators offer split range features 4-12 and 12-20 mA control, none offer the possibility of 12-4 and 20-12 mA control. This feature is valuable in certain applications where, for example two motors are employed to maintain an atmosphere. One motor is required to open 12-20 the other is required to open 12-4.

A more detailed and comprehensive list of all other features and specifications can be found in the Fives sales brochure [Bulletin 1615](#) and the [1615 Installation and Operation Guide](#).

WARNING: Situations dangerous to personnel and property may exist with the operation and maintenance of any combustion equipment. The presence of fuels, oxidants, hot and cold combustion products, hot surfaces, electrical power in control and ignition circuits, etc., are inherent with any combustion application. Components in combustion systems may exceed 160°F (71°C) surface temperatures and present hot surface contact hazard. Fives North American Combustion, Inc. suggests the use of combustion systems that are in compliance with all Safety Codes, Standards, Regulations and Directives; and care in operation.

CONTACT

fna.sales@fivesgroup.com

T +1 800 626 3477 - F +1 216 373 4237

Fives North American Combustion, Inc.
4455 East 71st Street - Cleveland, OH 44105 - USA
www.fivesgroup.com



fives
Industry can do it