

TABLE 1 - COMPLETE PIN NUMBER DESCRIPTION (CONT'D)

FEATURE	FEATURE DESCRIPTION	OPTION	OPTION DESCRIPTION
FLOADEFF	Full Load Efficiency (PIN 9)		For Marketing Purpose Only!
PLOADEFF	Part Load Efficiency (PIN 10)		For Marketing Purpose Only!
SOUND	Sound (PIN 11)		For Marketing Purpose Only!
VOLTAGE	Voltage (PIN 12, 13)	17	200/3/60
		28	230/3/60
		40	380/3/60
		42	400/3/60
		46	460/3/60
		50	380-415/3/50
		58	575/3/60
MODLVL	Modification Level (PIN 14)	B	Modification level
REF	Refrigerant (PIN 15)	A	R-134a Refrigerant
STARTERTYP	Starter Type (PIN 16)	V	Standard VSD
		R*	VSD with Active Filter
		Q	Special quote
POWERFLD	Power Field (PIN 17)	B	SP Circuit Breaker w/ Lockable Handle
		D	MP Supply TB
		M	MP Circuit Breaker w/Lockable Handle
		N	SP NF Disconnect Switch w/Lockable Handle
		O	SP Supply TB w/Individual Disconnect Switch
		P	MP NF Disconnect Switch w/ Lockable Handle
		S	SP Supply TB
		T	SP Supply TB w/Individual Circuit Breaker
PIN18	PIN 18	X	No selection
		Q	Special quote
PANELOPT	Panel Options (PIN 19)	X	No selection
		O	Convenience outlet
		M*	Convenience Outlet with KW meter
		W*	KW meter
		Q	Special quote
AMB	Ambient Kits (PIN 20)	X	No selection
		B*	Both Low and High Ambient kits
		H	High Ambient kit
		L*	Low Ambient kit
		Q	Special quote
BAS	BAS Reset/Offset (PIN 21)	X	No selection
		B	BAS/EMS Both Temp and Current Reset/Offset
		C	BAS/EMS Current Reset/Offset
		E	E-Link Kit (factory mounted, field commissioned) BACnet/Modbus/N2 output
		L	E-Link Kit (factory mounted, field commissioned) LON output
		T	BAS/EMS Temp Reset/Offset
		Q	Special quote

NOTE: * Option has not yet been designed