

TABLE 106 - VIBRATION ISOLATORS

ONE INCH DEFLECTION SPRING ISOLATOR CROSS REFERENCE					
WEIGHT RANGE (LBS)	WEIGHT RANGE (KG.)	VENDOR PART NUMBER	COLOR	PART NUMBER	SAP NUMBER
FOR UNITS WITH ALL POINT LOADS LESS THAN 1404 LBS. (637 KG)					
UP to 435 LBS	UP to 197	CP-1D-510	Black	029 25334 002	433668
435 to 766 LBS	197 to 347	CP-1D-900	Dark Green	029 25334 003	433669
766 to 1021 LBS	347 to 463	CP-1D-1200	Gray	029 25334 004	433670
1021 to 1157 LBS	463 to 525	CP-1D-1360	White	029 25334 005	433871
1157 to ***1785 LBS	525 to 810	CP-1D-1785N	Gray/Red	029 25334 006	433872
FOR UNITS WITH ANY POINT LOADS LESS THAN 1404 LBS. (637 KG)					
UP to 1149 LBS	UP to 521	C2P-1D-1350	Dark Purple	029 25334 008	433997
1149 to 1531 LBS	521 to 694	C2P -1D-1800	Dark Green	029 25334 009	433998
1531 to 2041 LBS	694 to 926	C2P-1D-2400	Gray	029 25334 010	433999
2041 to 2313 LBS	926 to 1049	C2P-1D-2720	White	029 25334 012	434000
2313 to ***3570 LBS	1049 to 1619	C2P-1D-3570N	Gray/Red	029 25334 013	434001

NEOPRENE ISOLATOR CROSS REFERENCE					
**WEIGHT RANGE (LBS)	WEIGHT RANGE (KG.)	VENDOR PART NUMBER	COLOR	PART NUMBER	SAP NUMBER
UP to 826 LBS	UP to 375	RD-3 Charcoal-WR	Charcoal	029 25335 001	434002
826 to 1689 LBS	375 to 766	RD-4 Brick Red-WR	Brick Red	029 25335 002	434004
1689 to ***4000 LBS	766 to 1814	RD-4 Charcoal-WR	Charcoal	029 25335 004	434005

TWO INCH DEFLECTION SEISMIC ISOLATOR CROSS REFERENCE					
WEIGHT RANGE (LBS)	WEIGHT RANGE (KG.)	VENDOR PART NUMBER	COLOR	PART NUMBER	SAP NUMBER
UP to 392 LBS	UP to 178	Y2RSI-2D-460	Green	029 25336 006	688690
392 to 605 LBS	178 to 274	Y2RSI-2D-710	Dark Brown	029 25336 008	688691
605 to 741 LBS	274 to 336	Y2RSI-2D-870	Red	029 25336 009	688692
741 to 1021 LBS	336 to 463	Y2RSI-2D-1200N	Red/Black	029 25336 010	688693
1021 to 1438 LBS	463 to 652	Y2RSI-2D-1690	Pink	029 25336 011	688694
1438 to 2245 LBS	652 to 1018	Y2RSI-2D-2640N	Pink/Gray	029 25336 012	688695
2245 to 2619 LBS	1018 to 1188	Y2RSI-2D-2870N	Pink/Gray/Orange	029 25336 013	688697
2619 to ***3740 LBS	1188 to 1696	Y2RSI-2D-3280N	Pink/Gray/Dark Brown	029 25336 014	688698

NOTES: * Value is de-rated by 15%

**Value is de-rated by 25%

***Value is not de-rated

Isolators with 1" deflection (PIN 55=1) must be of the same class for the entire unit. IE. Must use C2P's at all locations on a selected unit, or all CP's.

Reference M-1021 (QTC4 Weights and Isolators Standard) for isolators selection program.